NSN 5985-00-689-1923

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-00-689-1923

Body Material:
Metal
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
1.938 inches
Overall Diameter:
0.562 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
1.0 watts average
Rf Signal Attenuation In Decibels:
•
10.0
-
10.0
10.0 Attenuation Accuracy Reference Frequency:
10.0 Attenuation Accuracy Reference Frequency: 2.0 gigahertz
10.0 Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels:
10.0 Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00
10.0 Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight:
10.0 Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight: 1.500 ounces
Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight: 1.500 ounces Mounting Method:
Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight: 1.500 ounces Mounting Method: Connector
Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight: 1.500 ounces Mounting Method: Connector Terminal Type And Quantity:
Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight: 1.500 ounces Mounting Method: Connector Terminal Type And Quantity: 2 connector
Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight: 1.500 ounces Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight: 1.500 ounces Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz
Attenuation Accuracy Reference Frequency: 2.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Unpackaged Unit Weight: 1.500 ounces Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Fsc Application Data:

NSN 5985-00-689-1923

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000