NSN 5985-00-693-4389

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-693-4389

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

82.0 second bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches first flange and 0.903 inches first flange

Flange Inside Height:

0.397 inches first flange and 0.403 inches first flange

Flange Outside Width:

1.625 inches first flange

Flange Outside Height:

1.625 inches first flange

Voltage Standing Wave Ratio:

1.16

Waveguide Outside Width:

Between 1.003 inches and 1.006 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.897 inches and 0.903 inches

Waveguide Inside Height:

Between 0.397 inches and 0.403 inches

Waveguide Outside Height:

Between 0.503 inches and 0.505 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

13.188 inches

Waveguide Center To Center Distance:

7.281 inches

Flexibility:

Rigid single tubing segment

NSN 5985-00-693-4389 Waveguide Assembly - Page 2 of 2



Material:
Copper alloy all tubing segment and flange
Precious Material And Location:
All surfaces silver
Precious Material:
Silver
Surface Treatment:
Enamel all tubing segment and flange outside surfaces
Style Designator:
Offset bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0