NSN 5985-00-694-1224

Variable Attenuator - Page 1 of 2

Application Design:

Cylindrical w/side terminals

Audio

Body Style:

Overall Length:



View Online at https://aerobasegroup.com/nsn/5985-00-694-1224

3.000 inches
Overall Width:
3.094 inches
Body Diameter:
2.750 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Body Length:
2.062 inches
Schematic Diagram Designator:
Balanced "h"
Distance Between Mounting Facility Centers:
1.500 inches
Power Rating:
600.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
30
Address of the Book of the Book of the
Attenuation Per Step In Decibels:
2.0
·
2.0
2.0 Mounting Facility Type And Quantity:
2.0 Mounting Facility Type And Quantity: 2 threaded hole
2.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range:
2.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz
2.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Mounting Thread Quantity:
2.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Mounting Thread Quantity: 32 per inch
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:

NSN 5985-00-694-1224

Variable Attenuator - Page 2 of 2



Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
10000.0 input-output
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0