## NSN 5985-00-697-1469

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-697-1469 **Application Design:** Audio **Body Style:** Cylindrical w/rear terminals **Overall Length:** 3.062 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.938 inches **Body Length:** 2.124 inches **Overall Diameter:** 1.750 inches **Schematic Diagram Designator:** Unbalanced ladder **Distance Between Mounting Facility Centers:** 1.062 inches **Mounting Facility Screw Thread Series Designator:** Unc **Overall Attenuation Range In Decibels:** +0.0/+40.0 **Attenuation Variation Method:** Stepped **Step Position Quantity:** 20 **Attenuation Per Step In Decibels: Mounting Facility Type And Quantity:** 2 threaded hole Frequency Range: Between 0.000 hertz and 10.000 kilohertz **Overall Attenuation Accuracy In Decibels:** -1.00/+1.00 **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 shaft **Mounting Facility Pattern:** Two position in-line **Shaft Type:** 

Round

## NSN 5985-00-697-1469

Variable Attenuator - Page 2 of 2



Mounting Facility	Screw	Thread	Diameter:
0.138 inches			

Impedance Rating In Ohms:

250.0 input and 125.0 output

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A223a0