## NSN 5985-00-697-1469

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-697-1469

Application	Design:
	- • • · . g

Audio

**Body Style:** 

Cylindrical w/rear terminals

**Overall Length:** 

3.062 inches

Shaft Diameter:

0.249 inches

Shaft Length:

0.938 inches

**Body Length:** 

2.124 inches

**Overall Diameter:** 

1.750 inches

Schematic Diagram Designator:

Unbalanced ladder

**Distance Between Mounting Facility Centers:** 

1.062 inches

Mounting Facility Screw Thread Series Designator:

Unc

**Overall Attenuation Range In Decibels:** 

+0.0/+40.0

**Attenuation Variation Method:** 

Stepped

**Step Position Quantity:** 

20

Attenuation Per Step In Decibels:

2.0

Mounting Facility Type And Quantity:

2 threaded hole

Frequency Range:

Between 0.000 hertz and 10.000 kilohertz

**Overall Attenuation Accuracy In Decibels:** 

-1.00/+1.00

**Mounting Thread Quantity:** 

32 per inch

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Two position in-line

Shaft Type:

Round

## NSN 5985-00-697-1469

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.138 inches

Impedance Rating In Ohms:

250.0 input and 125.0 output

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A223a0