

View Online at <https://aerobasegroup.com/nsn/5985-00-699-8095>

Thread Class:

2b mounting facility hole

Body Style:

Rectangular

Overall Length:

2.000 inches

Overall Height:

2.000 inches

Overall Width:

1.813 inches

Frequency Rating:

0.0 gigahertz and 4.0 gigahertz single frequency voltage standing wave ratio

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

0.875 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.687 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.40 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

Bnc

Connector End Design:

Female

Rf Power Handling Capability:

3.0 kilowatts peak single

Minimum Crosstalk Rating In Decibels:

75.0 single

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

115.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

15.0 milliseconds

Pole Quantity:

1

Throw Quantity:

2

Rf Maximum Voltage Rating:

1.0 kilovolts rms

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.112 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Copper alloy body

Precious Material And Location:

Body silver

Precious Material:

Silver

Surface Treatment:

Silver body outside surfaces

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

2 tab, solder lug and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0