NSN 5985-00-710-4500

Variable Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-00-710-4500

Transmission line
Body Style:
Cylindrical w/rear terminals
Overall Length:
3.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Body Length:
2.062 inches
Overall Diameter:
2.250 inches
Schematic Diagram Designator:
Balanced "h"
Distance Between Mounting Facility Centers:
1.500 inches
Power Rating:
1.5 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+100.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
10 Attenuation Per Step In Decibels:
Attenuation Per Step In Decibels:
Attenuation Per Step In Decibels: 10.0
Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity:
Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole
Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range:
Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 1.000 megahertz
Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 1.000 megahertz Overall Attenuation Accuracy In Decibels:
Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 1.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50
Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 1.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity:
Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 1.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 32 per inch

Two position in-line

NSN 5985-00-710-4500

Variable Attenuator - Page 2 of 2



Fiig: A223a0