

View Online at <https://aerobasegroup.com/nsn/5985-00-711-9287>

Application Design:

Waveguide

Body Material:

Brass

Body Style:

Rectangular, terminal/terminals on opposite surfaces

Body Surface Treatment:

Enamel, baked

Overall Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.280 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.220 inches

Overall Height:

1.625 inches

Overall Width:

1.625 inches

Mounting Hole/stud Quantity:

8

Inside Width:

0.505 inches

Unthreaded Mounting Hole Diameter:

0.169 inches

Inside Height:

1.003 inches

Voltage Standing Wave Ratio:

1.20

Power Rating:

2.0 watts average and 1.0 kilowatts peak

Rf Signal Attenuation In Decibels:

10.0

Waveguide Flange Type:

Cover

Waveguide Flange Designation:

Ug-39/u

Attenuation Accuracy In Decibels:

-0.20/+0.20

Waveguide Designation:

Rg-52/u

Mounting Method:

Unthreaded hole

Terminal Type And Quantity:

2 flange

Frequency Range:

Between 8.200 gigahertz and 12.400 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000