

View Online at <https://aerobasegroup.com/nsn/5985-00-723-4524>

**Thread Class:**

2b mounting facility hole

**Body Style:**

Rectangular

**Overall Length:**

Between 2.345 inches and 2.405 inches

**Overall Height:**

1.940 inches

**Overall Width:**

Between 1.380 inches and 1.440 inches

**Frequency Rating:**

1350.0 megahertz and 1450.0 megahertz single frequency voltage standing wave ratio

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

1.032 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

0.562 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

1.15 single

**Insertion Loss In Decibels:**

0.20 single

**Coaxial Connector Series Designation:**

N

**Connector End Design:**

Female

**Rf Power Handling Capability:**

100.0 watts average single

**Minimum Crosstalk Rating In Decibels:**

27.0 single

**Actuator Operating Method:**

Relay

**Actuator Voltage In Volts:**

26.0

**Switch Operation Sequence:**

Breaks before makes

**Switching Time:**

25.0 milliseconds

**Switch Return Mechanism Type:**

Fail-safe

**Pole Quantity:**

1

**Throw Quantity:**

2

**Rf Maximum Voltage Rating:**

1.0 kilovolts peak

**Coupling Position Quantity:**

3

**Mounting Facility Type And Quantity:**

8 threaded hole

**Thread Qty Per Inch (tpi):**

40 mounting facility hole

**Thread Size:**

0.112 inches mounting facility hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Special Features:**

4 mtg holes each side of switch; enclosed housing to exclude sand and dust

**Thread Series Designator:**

Unc mounting facility hole

**Terminal Type And Quantity:**

2 turret and 3 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0