

View Online at <https://aerobasegroup.com/nsn/5985-00-727-3590>

**Application Design:**

Transmission line

**Body Style:**

Coaxial type

**Overall Length:**

3.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.750 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.562 inches

**Overall Height:**

2.875 inches

**Overall Width:**

2.125 inches

**Unthreaded Mounting Hole Diameter:**

0.144 inches

**Power Rating:**

5.0 watts average

**Overall Attenuation Range In Decibels:**

+0.0/+18.0

**Attenuation Accuracy Reference Frequency:**

60.0 kilohertz

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

3

**Attenuation Per Step In Decibels:**

6.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Frequency Range:**

Between 0.000 kilohertz and 60.000 kilohertz

**Overall Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Segment Attenuation Range In Decibels:**

+0.00/+6.00 and +6.00/+12.00 and +12.00/+18.00

**Segment Attenuation Accuracy In Decibels:**

-0.15/+0.16 and -0.17/+0.17 and -0.17/+0.18

**Adjustment Device Type And Quantity:**

3 pushbutton

**Mounting Facility Pattern:**

Four position rectangular

**Impedance Rating In Ohms:**

600.0 input-output

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A223a0