

View Online at <https://aerobasegroup.com/nsn/5985-00-727-3590>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.562 inches

Overall Height:

2.875 inches

Overall Width:

2.125 inches

Unthreaded Mounting Hole Diameter:

0.144 inches

Power Rating:

5.0 watts average

Overall Attenuation Range In Decibels:

+0.0/+18.0

Attenuation Accuracy Reference Frequency:

60.0 kilohertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

3

Attenuation Per Step In Decibels:

6.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 0.000 kilohertz and 60.000 kilohertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Segment Attenuation Range In Decibels:

+0.00/+6.00 and +6.00/+12.00 and +12.00/+18.00

Segment Attenuation Accuracy In Decibels:

-0.15/+0.16 and -0.17/+0.17 and -0.17/+0.18

Adjustment Device Type And Quantity:

3 pushbutton

Mounting Facility Pattern:

Four position rectangular

Impedance Rating In Ohms:

600.0 input-output

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0