## NSN 5985-00-729-4074

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-729-4074

| Application Design:  |
|--|
| Transmission line  |
| Body Style:  |
| Coaxial type   |
| Overall Length:  |
| 2.125 inches   |
| Overall Height:  |
| 2.000 inches   |
| Overall Width:   |
| 2.665 inches   |
|  |
| Voltage Standing Wave Ratio:                               |
| 1.30   |
| Coaxial Connector Series Designation:                      |
| Tnc  |
| Power Rating:  |
| 1.0 watts average  |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 0.2  |
| Overall Attenuation Range In Decibels:                     |
| +0.0/+10.0   |
| Attenuation Variation Method:                              |
| Stepped  |
| Step Position Quantity:                                    |
| 10   |
| Attenuation Per Step In Decibels:                          |
| 1.0  |
| Mounting Facility Type And Quantity:                       |
| 2 connector  |
| Frequency Range:   |
| Between 0.000 gigahertz and 1.300 gigahertz                |
| Overall Attenuation Accuracy In Decibels:                  |
| -0.30/+0.30  |
| Adjustment Device Type And Quantity:                       |
| 1 knob   |
| Impedance Rating In Ohms:                                  |
| 50.0 input-output  |
| Terminal Type And Quantity:                                |
| 2 connector, coaxial, female                               |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

-

## NSN 5985-00-729-4074

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0