NSN 5985-00-731-7391

Fixed Attenuator - Page 1 of 2



rixed Attenuator - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5985-00-731-7391
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
1.812 inches
Overall Diameter:
0.406 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Rf Signal Attenuation In Decibels:
40.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-1.00/+1.00
Unpackaged Unit Weight:
0.500 ounces
Mounting Method:

Mounting Method

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-00-731-7391

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000