## NSN 5985-00-739-1201

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-739-1201 **Application Design:** 

Transmission line

**Body Material:** 

Metal

**Body Style:** 

Round, terminal/terminals in opposite surface

**Body Surface Treatment:** 

Silver plated, qq-s-365

**Overall Length:** 

Between 2.100 inches and 2.300 inches

**Overall Diameter:** 

0.850 inches

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Voltage Standing Wave Ratio:** 

1.25

Input Impedance Rating In Ohms:

50.0

**Output Impedance Rating In Ohms:** 

50.0

**Coaxial Connector Series Designation:** 

Ν

**Power Rating:** 

4.0 watts average

**Rf Signal Attenuation In Decibels:** 

3.0

**Voltage Standing Wave Ratio Frequency Range:** 

+0.0/+2.5 gigahertz

**Attenuation Accuracy Reference Frequency:** 

100.0 megahertz

**Attenuation Accuracy In Decibels:** 

-0.30/+0.30

**Connection Type Per Function:** 

Male input and female output

**Unpackaged Unit Weight:** 

2.400 ounces

**Mounting Method:** 

Connector

**Terminal Type And Quantity:** 

2 connector

Frequency Range:

Between 0.000 hertz and 2.500 gigahertz

## NSN 5985-00-739-1201

Fixed Attenuator - Page 2 of 2



Precious Material And Location:
External surface silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A20000