NSN 5985-00-740-1307

Fixed Attenuator - Page 1 of 2



View	Online at https://aerobasegroup.com/nsn/5985-00-740-1307
Appl	ication Design:
Tran	smission line
Body	y Material:
Meta	I
Body	y Style:
Rour	nd, terminal/terminals in opposite surface
Body	y Surface Treatment:
Silve	r plated, qq-s-365
Over	all Length:
2.200) inches
Over	rall Diameter:
0.610) inches
Ope	rating Tempurature Range:
-55.0	/+125.0 degrees celsius
Volta	age Standing Wave Ratio:
1.25	
Inpu	t Impedance Rating In Ohms:
50.0	
Outp	out Impedance Rating In Ohms:
50.0	
Coax	kial Connector Series Designation:
Tnc	
Pow	er Rating:
2.0 v	vatts average
Rf S	ignal Attenuation In Decibels:
20.0	
Volta	age Standing Wave Ratio Frequency Range:
+0.0/	/+3.0 gigahertz
Atte	nuation Accuracy Reference Frequency:
2.5 g	igahertz
Atte	nuation Accuracy In Decibels:
-0.50	v/+0.50
Con	nection Type Per Function:
Fema	ale output and male input
Mou	nting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 3.000 gigahertz

Precious Material And Location:

Body surfaces silver

NSN 5985-00-740-1307 Fixed Attenuator - Page 2 of 2



Precious Material:	
Silver	
Fsc Application Data:	
Antennas, waveguides, and related equipment	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A20000