NSN 5985-00-755-2378



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-755-2378 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** 3.563 inches **Overall Diameter:** 0.875 inches **Voltage Standing Wave Ratio:** 1.10 and 1.20 and 1.35 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 1.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+1.0 gigahertz and +1.0/+3.0 gigahertz and +3.0/+4.0 gigahertz **Attenuation Accuracy Reference Frequency:** 4.0 gigahertz **Attenuation Accuracy In Decibels:** -0.60/+0.60 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 1.000 gigahertz and 4.000 gigahertz **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5985-00-755-2378

Fixed Attenuator - Page 2 of 2



Fiig:

A20000