NSN 5985-00-755-7885

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-755-7885

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
3.000 inches
Bolt Circle Diameter:
1.500 inches
Overall Width:
2.734 inches
Body Diameter:
2.344 inches
Shaft Diameter:
Between 0.249 inches and 0.251 inches
Shaft Length:
Between 0.907 inches and 0.969 inches
Body Length:
2.063 inches
Schematic Diagram Designator:
Bridged "t"
Distance Between Mounting Facility Centers:
1.500 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Power Rating:
1.5 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 525.000 kilohertz
Overall Attenuation Accuracy In Decibels:
0.75/.0.75

-0.75/+0.75

NSN 5985-00-755-7885

Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
600.0 input-output
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Terminal Type And Quantity:
6 tab, solder lug
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A223a0