## NSN 5985-00-760-4154

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-760-4154

## **Cross Sectional Shape:** Internal, rectangular external, rectangular **Thread Class:** 2b all flanges all connection facilities Thread Direction: Right-hand all flanges all connection facilities **Bend Angle In Deg:** 90.0 all bends e-plane **Tubing Wall Construction Style:** Seamless all tubing segment Flange Quantity: 2 Flange Inside Width: 1.020 inches second flange Flange Inside Height: 0.510 inches second flange Flange Outside Width: 1.688 inches second flange Flange Outside Height: 1.688 inches second flange Flange Depth: 0.510 inches second flange Flange Connecting Hole Diameter: 0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities **Voltage Standing Wave Ratio:** 1.15 **Insertion Loss In Decibels:** 0.10 Thready Qty Per Inch (tpi): 32 all flanges all connection facilities Maximum Operating Pressure: 20.0 pounds per square inch gage Waveguide Outside Width: 0.510 inches

**Thread Size:** 

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

1.020 inches

Waveguide Inside Height:

1.148 inches

Waveguide Outside Height:

0.638 inches

## NSN 5985-00-760-4154



Waveguide Assembly - Page 2 of 2 Waveguide Longer Offset Distance: 6.938 inches Flange Connecting Facility And Quantity: 4 unthreaded hole first flange single connection facility Waveguide Offset Distance: 1.740 inches Flexibility: Rigid all tubing segment Material: Aluminum all flange Surface Treatment: Enamel all tubing segment outside surfaces Style Designator: Bend type **Thread Series Designator:** Unc all flanges all connection facilities Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A073a0