NSN 5985-00-760-4159

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-760-4159

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.020 inches second flange

Flange Inside Height:

0.510 inches second flange

Flange Outside Width:

1.688 inches second flange

Flange Outside Height:

1.688 inches second flange

Flange Depth:

0.500 inches second flange

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.13

Insertion Loss In Decibels:

0.15

Thready Qty Per Inch (tpi):

32 all flanges all connection facilities

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

1.148 inches

Thread Size:

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

1.020 inches

Waveguide Inside Height:

0.510 inches

Waveguide Outside Height:

0.638 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

NSN 5985-00-760-4159 Waveguide Assembly - Page 2 of 2



Flange Style:
Choke type first flange
Waveguide Leg Length:
0.750 inches
Waveguide Longer Leg Length:
4.875 inches
Waveguide Center To Center Distance:
4.421 inches
Flexibility:
Rigid all tubing segment
Material:
Aluminum all flange
Surface Treatment:
Enamel all tubing segment outside surfaces
Style Designator:
U-bend type
Thread Series Designator:
Unc all flanges all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0