

View Online at <https://aerobasegroup.com/nsn/5985-00-761-6033>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.705 inches second flange

**Flange Inside Height:**

0.394 inches second flange

**Flange Outside Width:**

1.312 inches second flange

**Flange Outside Height:**

1.312 inches second flange

**Flange Depth:**

0.375 inches first flange

**Flange Connecting Hole Diameter:**

0.144 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.13

**Thread Qty Per Inch (tpi):**

32 first flange all connection facilities

**Maximum Operating Pressure:**

60.0 pounds per square inch gage

**Waveguide Outside Width:**

0.702 inches

**Thread Size:**

0.138 inches first flange all connection facilities

**Waveguide Inside Width:**

0.622 inches

**Waveguide Inside Height:**

0.311 inches

**Waveguide Outside Height:**

0.391 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Length:**

6.000 feet

**Special Features:**

Test data document: a81349-mil-w-287

**Flexibility:**

Flexible single tubing segment

**Material:**

Rubber synthetic single tubing jacket

**Precious Material And Location:**

Flange surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver all flange all surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc first flange all connection facilities

**Specification Data:**

81349-mil-w-287/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0