

View Online at <https://aerobasegroup.com/nsn/5985-00-761-6042>

Unable To Decode:

Internal, rectangular double ridged external, rectangular

Thread Class:

2b second flange first connection facility

Thread Direction:

Right-hand second flange first connection facility

Unable To Decode:

Seamless second tubing segment

Flange Quantity:

2

Flange Connecting Hole Diameter:

0.140 inches first flange all connection facilities and 0.154 inches first flange all connection facilities

Voltage Standing Wave Ratio:

1.40

Waveguide Outside Width:

0.791 inches

Thread Size:

0.138 inches second flange first connection facility

Waveguide Inside Width:

0.691 inches

Waveguide Inside Height:

0.321 inches

Waveguide Outside Height:

0.421 inches

Flange Connecting Facility And Quantity:

2 unthreaded hole second flange second connection facility

Waveguide Length:

Between 70.470 inches and 70.503 inches

Special Features:

1st flange includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole; flexible portion covered w/molded neoprene or silicone jacket depending on use

Flexibility:

Rigid second tubing segment

Material:

Aluminum alloy all flange

Surface Treatment:

Enamel second tubing segment outside surfaces

Style Designator:

Straight type

Supplementary Features:

Marked one end tubing segment w/arrow and word up

Thread Series Designator:

Unc second flange first connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0