

View Online at <https://aerobasegroup.com/nsn/5985-00-761-6048>

**Unable To Decode:**

Internal, rectangular double ridged external, rectangular

**Unable To Decode:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.689 inches first flange and 0.693 inches first flange

**Flange Inside Height:**

0.319 inches first flange and 0.323 inches first flange

**Flange Outside Width:**

1.358 inches first flange and 1.390 inches first flange

**Flange Outside Height:**

1.358 inches first flange and 1.390 inches first flange

**Flange Depth:**

0.235 inches first flange and 0.255 inches first flange

**Flange Connecting Hole Diameter:**

0.143 inches first flange first connection facility and 0.149 inches first flange first connection facility

**Voltage Standing Wave Ratio:**

1.35

**Waveguide Outside Width:**

0.791 inches

**Waveguide Inside Width:**

0.691 inches

**Waveguide Inside Height:**

0.321 inches

**Waveguide Outside Height:**

0.421 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole first flange first connection facility

**Unable To Decode:**

Contact, double ridge type first flange

**Special Features:**

1st flange includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for ea mtg hole; 2nd flange not pressurized

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy all flange

**Surface Treatment:**

Enamel all tubing segment and flange outside surfaces

**Style Designator:**

Three bend type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0