NSN 5985-00-763-8025

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-763-8025

| Application Design: |
|---------------------------------------------------------------------------|
| Transmission line |
| Body Material: |
| Metal |
| Body Style: |
| Rectangular, terminal/terminals on opposite surfaces |
| Body Surface Treatment: |
| Enamel |
| Overall Length: |
| 17.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 16.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.938 inches |
| Overall Height: |
| 5.938 inches |
| Overall Width: |
| 8.500 inches |
| Mounting Hole/stud Quantity: |
| 4 |
| Operating Tempurature Range: |
| Any acceptable |
| Voltage Standing Wave Ratio: |
| 1.10 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| N |
| Power Rating: |
| 200.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 30.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0 to 500.0 megahertz |
| Mounting Facility Thread Size And Series/type Designator: |
| 0.250-20 unc |
| Attenuation Accuracy In Decibels: |
| -0.20 to 0.20 |
| Frequency Sensitivity Attenuation In Decibels: |

Not rated

NSN 5985-00-763-8025

Fixed Attenuator - Page 2 of 2



| Temperature Sensitivity Attenuation In Decibels: |
|--------------------------------------------------|
| Not rated |
| Connection Type Per Function: |
| Female input-output |
| Mounting Method: |
| Threaded hole |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 500.000 megahertz |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A20000 |