NSN 5985-00-764-2555

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-764-2555

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
7.840 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches
Overall Height:
2.846 inches
Overall Width:
2.160 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.686 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N
Power Rating:
25.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 2.900 gigahertz and 3.300 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Four position rectangular

Shaft Type:Round, slotted

NSN 5985-00-764-2555

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
.

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0