## NSN 5985-00-764-8602

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-764-8602

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Silver plated, qq-s-365
Overall Length:
2.690 inches
Overall Diameter:
0.830 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 3.0 kilowatts peak
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.5 gigahertz
Attenuation Accuracy Reference Frequency:
4.5 gigahertz
Attenuation Accuracy In Decibels:
-1.50/+1.50
Connection Type Per Function:
Female output and male input
Unpackaged Unit Weight:
2.800 ounces
Mounting Method:
Terminal
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 4.500 gigahertz
Between 6.000 nonz and 1.000 giganoriz

## **NSN 5985-00-764-8602** Fixed Attenuator - Page 2 of 2



Precious Material And Location:
Body silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia·

A20000