## NSN 5985-00-765-6585

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-765-6585 **Application Design:** Transmission line **Body Material:** Any acceptable **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** Between 1.880 inches and 1.940 inches **Overall Diameter:** Between 0.800 inches and 0.830 inches **Operating Tempurature Range:** +0.0/+60.0 degrees celsius **Voltage Standing Wave Ratio:** 1.35 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 1.0 watts average and 2.0 watts peak **Rf Signal Attenuation In Decibels:** 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.75/+0.75 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5985-00-765-6585

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000