## NSN 5985-00-767-1193

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-767-1193

Application Design:
Printed circuit board
Body Style:
Cylindrical w/side terminals
Overall Length:
4.813 inches
Overall Width:
1.210 inches
Body Diameter:
0.953 inches
Scale Linearity:
Linear
Shaft Diameter:
0.250 inches
Shaft Length:
3.562 inches
Body Length:
1.000 inches
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+150.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches
Impedance Rating In Ohms:

150.0 input-output

## NSN 5985-00-767-1193

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity	Terminal	<b>Type</b>	And	Quantity	<b>/</b> :
----------------------------	----------	-------------	-----	----------	------------

3 tab, solder lug

**Fsc Application Data:** 

Antennas, waveguides and related equip.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0