## NSN 5985-00-779-9130

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-779-9130

Application Design:						
Audio						
Body Style:						
Rotary switch type						
Overall Length:						
3.000 inches						
Shaft Diameter:						
0.250 inches						
Shaft Length:						
0.937 inches						
Overall Diameter:						
2.343 inches						
Schematic Diagram Designator:						
Bridged "t"						
Distance Between Mounting Facility Centers:						
1.500 inches						
Power Rating:						
0.6 watts average and 2.5 watts peak						
Mounting Facility Screw Thread Series Designator:						
Unc						
Overall Attenuation Range In Decibels:						
+0.0/+90.0						
Attenuation Variation Method:						
Stepped						
Step Position Quantity:						
9						
Attenuation Per Step In Decibels:						
10.0						
Mounting Facility Type And Quantity:						
2 threaded hole						
Mounting Thread Quantity:						
32 per inch						
Adjustment Device Type And Quantity:						
1 shaft						
Mounting Facility Pattern:						
Two position in-line						
Shaft Type:						
Round						
Mounting Facility Screw Thread Diameter:						
0.164 inches						
Impedance Rating In Ohms:						
1000.0 input-output						

## NSN 5985-00-779-9130

Variable Attenuator - Page 2 of 2



ī	ermina	ı	Type	Δnd	Qua	antity.
ı	CHILLING	41	INDE	Allu	wu	aiititv.

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0