NSN 5985-00-781-0314

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-781-0314

| Application Design: |
|--|
| Transmission line |
| Body Material: |
| Metal |
| Body Style: |
| Round, terminal/terminals in opposite surface |
| Body Surface Treatment: |
| Any acceptable |
| Overall Length: |
| 2.300 inches |
| Overall Diameter: |
| 0.625 inches |
| Voltage Standing Wave Ratio: |
| 1.15 and 1.25 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Bnc |
| Power Rating: |
| 2.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 3.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+1.0 gigahertz and +1.0/+1.5 gigahertz |
| Attenuation Accuracy Reference Frequency: |
| 1.5 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.40/+0.40 |
| Frequency Sensitivity Attenuation In Decibels: |
| 0.40 |
| Connection Type Per Function: |
| Female input and male output |
| Unpackaged Unit Weight: |
| 1.500 ounces |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 1.500 gigahertz |

NSN 5985-00-781-0314

Fixed Attenuator - Page 2 of 2



| Fsc Application Data | Fsc Appl | ication | Data |
|----------------------|----------|---------|------|
|----------------------|----------|---------|------|

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000