## NSN 5985-00-781-0314

View Online at https://aerobasegroup.com/nsn/5985-00-781-0314

## Fixed Attenuator - Page 1 of 2 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** 2.300 inches **Overall Diameter:** 0.625 inches **Voltage Standing Wave Ratio:** 1.15 and 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+1.0 gigahertz and +1.0/+1.5 gigahertz **Attenuation Accuracy Reference Frequency:** 1.5 gigahertz **Attenuation Accuracy In Decibels:** -0.40/+0.40 **Frequency Sensitivity Attenuation In Decibels:** 0.40 **Connection Type Per Function:** Female input and male output **Unpackaged Unit Weight:** 1.500 ounces **Mounting Method:** Connector **Terminal Type And Quantity:**

2 connector

**Frequency Range:** 

Between 0.000 hertz and 1.500 gigahertz

## NSN 5985-00-781-0314

Fixed Attenuator - Page 2 of 2



**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A20000