## NSN 5985-00-783-5143

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-783-5143

Application Design:
Audio
Body Style:
Cylindrical w/rear terminals
Overall Length:
1.938 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.500 inches
Shaft Length:
0.688 inches
Body Length:
1.250 inches
Overall Diameter:
0.875 inches
Schematic Diagram Designator:
"t"
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+50.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round, slotted
Mounting Facility Screw Thread Diameter:
0.375 inches

## NSN 5985-00-783-5143

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms	lmp	edance	Rating	In	<b>Ohms</b>
--------------------------	-----	--------	--------	----	-------------

600.0 input-output

**Terminal Type And Quantity:** 

9 tab, solder lug

Shelf Life:

-----

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0