

View Online at <https://aerobasegroup.com/nsn/5985-00-784-3494>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.362 inches all flanges and 0.364 inches all flanges

Flange Inside Height:

0.222 inches all flanges and 0.224 inches all flanges

Flange Outside Width:

0.745 inches all flanges and 0.755 inches all flanges

Flange Outside Height:

0.745 inches all flanges and 0.755 inches all flanges

Flange Depth:

0.182 inches all flanges and 0.192 inches all flanges

Flange Connecting Hole Diameter:

0.116 inches all flanges all connection facilities and 0.118 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.30

Insertion Loss In Decibels:

0.35

Maximum Operating Pressure:

60.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.358 inches and 0.362 inches

Waveguide Inside Width:

Between 0.2785 inches and 0.2815 inches

Waveguide Inside Height:

Between 0.1385 inches and 0.1415 inches

Waveguide Outside Height:

Between 0.218 inches and 0.222 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Length:

4.130 inches

Flexibility:

Flexible single tubing segment

Material:

Copper alloy all tubing segment and flange

Surface Treatment:

Enamel all flange outside surfaces

Style Designator:

Straight type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0