NSN 5985-00-791-7351

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-791-7351 **Application Design:** Audio **Body Material:** Plastic, epoxy resin **Body Style:** Rectangular, terminal/terminals on one surface **Terminal Material:** Copper **Overall Length:** Between 0.969 inches and 1.031 inches **Overall Height:** 0.595 inches **Overall Width:** Between 0.594 inches and 0.656 inches **Body Height:** Between 0.469 inches and 0.531 inches **Schematic Diagram Designator:** Balanced "h" bridged **Operating Tempurature Range:** -40.0/+85.0 degrees celsius **Input Impedance Rating In Ohms:** 600.0 **Output Impedance Rating In Ohms:** 600.0 **Power Rating:** 250.0 milliwatts average Rf Signal Attenuation In Decibels: 14.0 **Center To Center Distance Between First And Second Terminals:** 0.250 inches **Center To Center Distance Between Second And Third Terminals:** 0.500 inches **Center To Center Distance Between Third And Fourth Terminals:** 0.750 inches **Attenuation Accuracy Reference Frequency:** 1.0 kilohertz **Attenuation Accuracy In Decibels:** -0.14/+0.14 **Mounting Method: Terminal**

Terminal Type And Quantity:

4 banana plug

NSN 5985-00-791-7351

Fixed Attenuator - Page 2 of 2



Frequency Range:
Between 0.000 hertz and 1.000 kilohertz
Precious Material And Location:
Terminal surfaces silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides and related equip
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000