## NSN 5985-00-791-7362

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-791-7362

view Online at https://aerobasegroup.com/nsn/5985-00-791-7362
Application Design:
Audio
Body Material:
Plastic, epoxy resin
Body Style:
Rectangular, terminal/terminals on one surface
Terminal Material:
Copper
Terminal Surface Treatment:
Silver plated
Overall Length:
Between 0.969 inches and 1.031 inches
Overall Height:
0.594 inches
Overall Width:
Between 0.594 inches and 0.656 inches
Body Height:
Between 0.469 inches and 0.531 inches
Schematic Diagram Designator:
Balanced "h" bridged
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Input Impedance Rating In Ohms:
600.0
Output Impedance Rating In Ohms:
600.0
Power Rating:
250.0 milliwatts average
Rf Signal Attenuation In Decibels:
13.0
Center To Center Distance Between First And Second Terminals:
0.250 inches
Center To Center Distance Between Second And Third Terminals:
0.500 inches
Center To Center Distance Between Third And Fourth Terminals:
0.750 inches
Attenuation Accuracy Reference Frequency:
1.0 kilohertz
Attenuation Accuracy In Decibels:
-0.20/+0.20
Mounting Method:

Terminal

## NSN 5985-00-791-7362

Fixed Attenuator - Page 2 of 2



Terminal Type And Quantity:	
4 banana plug	
Frequency Range:	
Between 0.000 hertz and 1.000 kilohertz	
Precious Material And Location:	
Terminal surfaces silver	
Precious Material:	
Silver	
Fsc Application Data:	
Antennas, waveguides, and related equipment	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiia·	

A20000