NSN 5985-00-794-8766



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-794-8766 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Silver plated, qq-s-365 **Overall Length:** 2.200 inches **Overall Diameter:** 0.830 inches **Voltage Standing Wave Ratio:** Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+2.5 gigahertz **Attenuation Accuracy Reference Frequency:** 2.5 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Unpackaged Unit Weight:** 2.400 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

Frequency Range:

Between 0.000 hertz and 2.500 gigahertz

Precious Material And Location:

Body surfaces silver

Precious Material:

Silver

NSN 5985-00-794-8766

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc Appl	ication	Data
----------------------	----------	---------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000