## NSN 5985-00-802-7359

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-802-7359 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Silver plated, qq-s-365 **Overall Length:** 2.656 inches **Overall Diameter:** 0.578 inches **End Application:** Wsd: aircrafts, viking s-3a; orion p-3; stratolifter c-135; automated remote tracking station (arts); ticonderoga cg (47); tarawa lha; spruance dd (963); wasp lhd; kidd ddg; virginia cgn (41) Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms: Coaxial Connector Series Designation:** Bnc **Power Rating:** 1.0 watts average **Rf Signal Attenuation In Decibels:** 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+3.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and male output **Mounting Method: Terminal Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 3.000 gigahertz **Criticality Code Justification:** 

Feat

**Special Features:** 

Weapon system essential

**Precious Material And Location:** 

Body surface silver

## NSN 5985-00-802-7359

Fixed Attenuator - Page 2 of 2

A20000



Precious Material:
Silver
Test Data Document:
87557-6-217c0009 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiia: