

View Online at <https://aerobasegroup.com/nsn/5985-00-802-7540>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

180.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges

Flange Inside Height:

0.503 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.15

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

Flange Style:

Cover type all flanges

Waveguide Leg Length:

Between 3.297 inches and 3.328 inches

Waveguide Longer Leg Length:

Between 4.172 inches and 4.203 inches

Waveguide Center To Center Distance:

Between 3.766 inches and 3.797 inches

Waveguide Height:

Between 4.172 inches and 4.203 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber synthetic single tubing jacket

Precious Material And Location:

All surfaces rhodium

Precious Material:

Rhodium

Surface Treatment:

Rhodium all tubing segment and flange all surfaces

Style Designator:

U-bend type

Fsc Application Data:

Radar equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0