## NSN 5985-00-803-6202



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-803-6202 **Application Design:** Waveguide **Body Material: Brass Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Enamel **Overall Length:** 6.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.280 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.220 inches **Overall Height:** 1.625 inches **Overall Width:** 1.875 inches **Mounting Hole/stud Quantity: Inside Width:** 0.505 inches **Unthreaded Mounting Hole Diameter:** 0.169 inches **Inside Height:** 1.005 inches **Voltage Standing Wave Ratio:** 1.00 and 1.15 **Power Rating:** 1.0 watts average Rf Signal Attenuation In Decibels: **Waveguide Flange Type:** Cover **Waveguide Flange Designation:** Ug-39/u **Attenuation Accuracy In Decibels:** -0.08/+0.08 **Waveguide Designation:** 

Rg-52/u

**Mounting Method:** 

Terminal w/mounting holes

## NSN 5985-00-803-6202

Fixed Attenuator - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

2 flange

Frequency Range:

Between 8.200 gigahertz and 12.400 gigahertz

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000