## NSN 5985-00-805-7131

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-805-7131

## **Cross Sectional Shape:** Internal, rectangular external, rectangular **Thread Class:** 2b first flange all connection facilities Thread Direction: Right-hand first flange all connection facilities Bend Angle In Deg: 123.0 single bend h-plane **Tubing Wall Construction Style:** Seamless single tubing segment **Tubing Twist Type:** Straight twist single tubing segment **Tubing Twist Angle In Deg:** 4.0 single tubing segment Flange Quantity: 2 Flange Inside Width: 1.0625 inches second flange Flange Inside Height: 0.505 inches second flange Flange Outside Width: 1.625 inches second flange Flange Outside Height: 1.625 inches first flange Flange Inside Diameter: 1.225 inches first flange Flange Depth: 0.438 inches first flange Flange Connecting Hole Diameter: 0.169 inches second flange all connection facilities **Voltage Standing Wave Ratio:** 1.05 Thready Qty Per Inch (tpi): 32 first flange all connection facilities Waveguide Outside Width: 1.000 inches **Thread Size:** 0.164 inches first flange all connection facilities Waveguide Inside Width: 0.900 inches Waveguide Inside Height: 0.400 inches

## **NSN 5985-00-805-7131** Waveguide Assembly - Page 2 of 2



Waveguide Outside Height:
0.500 inches
Waveguide Longer Offset Distance:
3.390 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole second flange all connection facilities
Flange Style:
Cover type second flange
Waveguide Offset Distance:
1.915 inches
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy single tubing segment
Surface Treatment:
Chromate single tubing segment inside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0