## NSN 5985-00-810-0753

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-810-0753

| Application Design:   |
|---|
| Transmission line   |
| Body Style:   |
| Coaxial type  |
| Overall Length:   |
| 4.810 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 1.485 inches and 1.515 inches                                     |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| Between 1.485 inches and 1.515 inches                                     |
| Overall Height:   |
| 2.720 inches  |
| Overall Width:  |
| 2.000 inches  |
| Scale Linearity:  |
| Linear  |
| Scale Division Quantity:  |
| 8   |
| Shaft Diameter:   |
| Between 0.248 inches and 0.250 inches                                     |
| Shaft Length:   |
| 1.000 inches  |
| Connector Manufacturer Code:  |
| 97942   |
| Connector Manufacturer Part Number:                                       |
| Ug-447-u  |
| Operating Tempurature Range:  |
| -55.0/+120.0 degrees celsius  |
| Coaxial Connector Series Designation:                                     |
| Bnc   |
| Power Rating:   |
| 500.0 milliwatts peak   |
| Mounting Facility Screw Thread Series Designator:                         |
| Unc   |
| Insertion Loss At Minimum Attenuation In Maximum Decibels:                |
| 0.5   |
| Overall Attenuation Range In Decibels:                                    |
| +39.0/+43.0   |
| Attenuation Variation Method:   |
| Stepped   |
| Step Position Quantity:   |

8

## **NSN 5985-00-810-0753** Variable Attenuator - Page 2 of 2



| Attenuation Per Step In Decibels:               |
|---|
| 0.5   |
| Mounting Facility Type And Quantity:            |
| 4 threaded hole                                 |
| Frequency Range:                                |
| Between 125.000 megahertz and 225.000 megahertz |
| Mounting Thread Quantity:                       |
| 32 per inch                                     |
| Adjustment Device Type And Quantity:            |
| 1 shaft   |
| Mounting Facility Pattern:                      |
| Four position rectangular                       |
| Shaft Type:                                     |
| Round   |
| Mounting Facility Screw Thread Diameter:        |
| 0.164 inches                                    |
| mpedance Rating In Ohms:                        |
| 50.0 input-output                               |
| Special Features:                               |
| Mark under connectors symbols j10 and j11       |
| Terminal Type And Quantity:                     |
| 2 connector, coaxial, male                      |
| Shelf Life:                                     |
| N/a   |
| Unit Of Measure:                                |
| -   |
| Demilitarization:                               |
| No  |
| Fiig:   |
| A223a0  |
|   |