

NSN 5985-00-810-2464 Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-810-2464 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Silver plated, qq-s-365 **Overall Length:** 2.750 inches **Overall Diameter:** 0.947 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 2.0 watts average and 3.0 kilowatts peak

Rf Signal Attenuation In Decibels:

15.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+5.0 gigahertz

Attenuation Accuracy In Decibels:

-0.75/+0.75

Connection Type Per Function:

Female output and male input

Unpackaged Unit Weight:

2.800 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 5.000 gigahertz

Precious Material And Location:

Body surfaces silver

NSN 5985-00-810-2464 Fixed Attenuator - Page 2 of 2



Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A20000