## NSN 5985-00-811-0305

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-811-0305 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** Between 1.185 inches and 1.235 inches **Overall Diameter:** Between 0.370 inches and 0.390 inches **Operating Tempurature Range:** -10.0/+55.0 degrees celsius **End Application:** Test set, countermeasures an/alm-69 **Voltage Standing Wave Ratio:** 1.25 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Osm **Power Rating:** 250.0 milliwatts average Rf Signal Attenuation In Decibels: 30.0 **Voltage Standing Wave Ratio Frequency Range:** +0.9/+1.1 megahertz **Attenuation Accuracy In Decibels:** -0.25/+0.25 **Connection Type Per Function:** Female input and male output **Unpackaged Unit Weight:** 0.300 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

Frequency Range:

Between 0.900 megahertz and 1.100 megahertz

## NSN 5985-00-811-0305

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc A	oplicatio	n Data:
----------------------	-------	-----------	---------

Microwave equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000