NSN 5985-00-811-0307

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-811-0307

Application Design:				
Transmission line				
Body Material:				
Metal				
Body Style:				
Err-090				
Body Surface Treatment:				
Any acceptable				
Overall Length:				
Between 1.185 inches and 1.235 inches				
Overall Diameter:				
Between 0.370 inches and 0.390 inches				
Operating Tempurature Range:				
-40.0/+55.0 degrees celsius				
End Application:				
Test set, countermeasures an/alm-69				
Voltage Standing Wave Ratio:				
1.35				
Input Impedance Rating In Ohms:				
50.0				
Output Impedance Rating In Ohms:				
50.0				
Coaxial Connector Series Designation:				
Osm				
Power Rating:				
250.0 milliwatts average				
Rf Signal Attenuation In Decibels:				
20.0				
Voltage Standing Wave Ratio Frequency Range:				
+140.0/+180.0 megahertz				
Attenuation Accuracy Reference Frequency:				
180.0 megahertz				
Attenuation Accuracy In Decibels:				
-0.25/+0.25				
Connection Type Per Function:				
Female input and male output				
Mounting Method:				
Connector				
Terminal Type And Quantity:				
2 connector				
Frequency Range:				
Retween 140 000 megahertz and 180 000 megahertz				

NSN 5985-00-811-0307

Fixed Attenuator - Page 2 of 2



	Fsc	Ap	olication	Data:
--	-----	----	-----------	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000