## NSN 5985-00-811-0307

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-811-0307

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
Between 1.185 inches and 1.235 inches
Overall Diameter:
Between 0.370 inches and 0.390 inches
Operating Tempurature Range:
-40.0/+55.0 degrees celsius
End Application:
Test set, countermeasures an/alm-69
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Osm
Power Rating:
250.0 milliwatts average
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+140.0/+180.0 megahertz
Attenuation Accuracy Reference Frequency:
180.0 megahertz
Attenuation Accuracy In Decibels:
-0.25/+0.25
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 140 000 megahertz and 180 000 megahertz

## NSN 5985-00-811-0307

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc Appl	ication	Data
----------------------	----------	---------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000