

View Online at <https://aerobasegroup.com/nsn/5985-00-821-2103>

**Cross Sectional Shape:**

Internal, round external, round

**Thread Direction:**

Right-hand all flanges single connection facility

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Tubing Twist Type:**

Twistable single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.708 inches all flanges and 0.712 inches all flanges

**Flange Inside Height:**

0.309 inches all flanges and 0.313 inches all flanges

**Flange Outside Width:**

1.312 inches all flanges

**Flange Outside Height:**

1.312 inches all flanges

**Flange Inside Diameter:**

0.620 inches all flanges and 0.624 inches all flanges

**Flange Depth:**

0.375 inches all flanges

**Voltage Standing Wave Ratio:**

1.06

**Insertion Loss In Decibels:**

0.15

**Maximum Operating Pressure:**

45.0 pounds per square inch gage

**Thread Size:**

0.138 inches all flanges single connection facility

**Waveguide Outside Diameter:**

0.950 inches

**Flange Connecting Facility And Quantity:**

4 threaded hole all flanges single connection facility

**Flange Style:**

Choke type all flanges

**Waveguide Length:**

4.375 inches

**Waveguide Center To Center Distance:**

0.475 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Rubber synthetic single tubing jacket

**Surface Treatment:**

Copper single tubing segment all surfaces

**Style Designator:**

Offset bend type

**Thread Series Designator:**

Unc all flanges single connection facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0