

View Online at <https://aerobasegroup.com/nsn/5985-00-821-2103>

Cross Sectional Shape:

Internal, round external, round

Thread Direction:

Right-hand all flanges single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.708 inches all flanges and 0.712 inches all flanges

Flange Inside Height:

0.309 inches all flanges and 0.313 inches all flanges

Flange Outside Width:

1.312 inches all flanges

Flange Outside Height:

1.312 inches all flanges

Flange Inside Diameter:

0.620 inches all flanges and 0.624 inches all flanges

Flange Depth:

0.375 inches all flanges

Voltage Standing Wave Ratio:

1.06

Insertion Loss In Decibels:

0.15

Maximum Operating Pressure:

45.0 pounds per square inch gage

Thread Size:

0.138 inches all flanges single connection facility

Waveguide Outside Diameter:

0.950 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Length:

4.375 inches

Waveguide Center To Center Distance:

0.475 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber synthetic single tubing jacket

Surface Treatment:

Copper single tubing segment all surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc all flanges single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0