NSN 5985-00-824-7959

Variable Attenuator - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5985-00-824-7959

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.040 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.500 inches
Overall Height:
2.410 inches
Overall Width:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.500 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N .
Power Rating:
3.5 kilowatts average
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 2.900 gigahertz and 3.100 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Test Data Document:
97942-128c361h02 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:

NSN 5985-00-824-7959

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0