NSN 5985-00-829-5364

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-829-5364

3
Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
6.1458 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.875 inches
Overall Height:
2.516 inches
Overall Width:
2.516 inches
Operating Tempurature Range:
-0.0/+50.0 degrees celsius
Power Rating:
1.5 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+25.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 5.000 hertz and 33.000 hertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 motor
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female and 8 turret
Shelf Life:

N/a

NSN 5985-00-829-5364

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0