NSN 5985-00-830-4259

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-830-4259

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches all flanges and 1.256 inches all flanges

Flange Inside Height:

0.628 inches all flanges and 0.631 inches all flanges

Flange Outside Width:

1.860 inches all flanges and 1.890 inches all flanges

Flange Outside Height:

1.860 inches all flanges and 1.890 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Length:

7.000 inches

Waveguide Center To Center Distance:

3.160 inches

Special Features:

Waveguide flanges are double type each end

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy all tubing segment and flange

NSN 5985-00-830-4259

Waveguide Assembly - Page 2 of 2



Surface Treatment:

Chromate zinc single tubing segment all surfaces

Style Designator:

Offset bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0