# NSN 5985-00-833-2432

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-833-2432

## **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** 1b round, terminal/terminals in opposite surface **Terminal Material:** Steel, stainless **Terminal Surface Treatment:** Passivated **Body Surface Treatment:** Passivated **Overall Length:** 1.400 inches **Overall Diameter:** 0.370 inches **Operating Tempurature Range:** +0.0/+65.0 degrees celsius Voltage Standing Wave Ratio: 1.20 and 1.35 and 1.75 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 1.0 watts average and 500.0 watts peak **Rf Signal Attenuation In Decibels:** 10.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50**Connection Type Per Function:** Female output and male input Unpackaged Unit Weight: 0.700 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

# NSN 5985-00-833-2432

Fixed Attenuator - Page 2 of 2



Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

#### Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

Fiig:

A20000